

1154-CN-0 Series

Light Duty Wire & Shelving/Display (Octagon Raceway)

- Light-duty, economical choice, for display racks, etc.


Load
35-90 kg



» Features



Axle Lock Brake



Bumper



Octagon Raceway

» Wheel Options



PU on PP Core



TPR on PP Core



Rubber



PVC on PP Core



Resolute



PP



PU



Ball Bearing



Plain Ball Bearing

» THREADED STEM SPECIFICATION

Suffix	Threaded Size
3" 4" 5"	5/16 x 19mm

 Diameter×Width	 Load	 Material	 Item No.			 Bearing	 Overall Height	 Swivel radius
			Fixed	Swivel	Brake			
75mmx21mm (3"x7/8")	50 kgs (110 lbs)	PU on PP Core	—	1154-O-03-31-2	1154-O-03-31-4	Plain Bearing	93 mm (3-11/16")	Swivel 68mm Swivel W/Side Brake 68mm
	50 kgs (110 lbs)	Rubber	—	1154-O-03-06-2	1154-O-03-06-4			
75mmx24mm (3"x15/16")	60 kgs (130 lbs)	PU	—	1154-O-03-88-2	—	Ball Bearing	93 mm (3-11/16")	Swivel 68mm
75mmx25 mm (3"x1")	70 kgs (155 lbs)	PVC on PP Core	—	1154-O-03-27-2	1154-O-03-27-4	Plain Bearing	93 mm (3-11/16")	Swivel 68mm Swivel W/Side Brake 68mm
	60 kgs (130 lbs)	Rubber	—	1154-O-03-06-2	1154-O-03-06-4			
	70 kgs (155 lbs)	TPR on PP Core	—	1154-O-03-75-2	1154-O-03-75-4			
	70 kgs (155 lbs)	PP	—	1154-O-03-29-2	1154-O-03-29-4			
100mmx24mm (4"x15/16")	70 kgs (155 lbs)	PU	—	1154-O-04-88-2	—	Ball Bearing	116 mm (4-3/5")	Swivel 81mm
100mmx25mm (4"x1")	70 kgs (155 lbs)	PU on PP Core	—	1154-O-04-31-2	1154-O-04-31-4	Plain Bearing	116 mm (4-3/5")	Swivel 81mm Swivel W/Side Brake 81mm
	70 kgs (155 lbs)	TPR on PP Core	—	1154-O-04-75-2	1154-O-04-75-4			
	70 kgs (155 lbs)	Rubber	—	1154-O-04-06-2	1154-O-04-06-4			
	90 kgs (198 lbs)	PP	—	1154-O-04-29-2	1154-O-04-29-4			
125mmx25mm (5"x1")	90 kgs (198 lbs)	PU on PP Core	—	1154-O-05-31-2	1154-O-05-31-4	Plain Bearing	142 mm (5-3/5")	Swivel 93mm Swivel W/Side Brake 93mm
	80 kgs (176 lbs)	TPR on PP Core	—	1154-O-05-75-2	1154-O-05-75-4			
	90 kgs (198 lbs)	Rubber	—	1154-O-05-06-2	1154-O-05-06-4			