

1101 Series

D Type Pneumatic Caster (American Style)

- Double ball bearing swivel raceway.
Yoke: bright zinc-plated or chrome-plated.

Load
100-125 kg



» Wheel Options



Pneumatic with painted steel rim



Pneumatic with plastic rim



Pneumatic with plated steel rim



Solid Rubber wheel with painted steel rim



Solid Rubber wheel with plated steel rim



Ball Bearing

» TOP PLATE SIZE AND BOLT HOLE SPACING

Suffix	Top Plate Size	Bolt Hole Spacing	Attaching Bolt Size
1	115 x 100 mm (4-1/2"x 3-15/16")	85 x 70 mm (3-5/16"X 2-3/4")	11 mm (7/16")
2	115 x 159 mm (4-1/2"x 6-1/4")	75 x 130mm (2-7/16"~3-3/8"x 4-15/16"~5-1/4")	12.7 mm (1/2")
3	100 x 144 mm (3-15/16"x 4-1/2")	75 x 120 mm (3"x 4-3/4")	12 mm (1/2")

Diameter×Width 	Load 	Material 	Item No. 			Bearing 	Overall Height 	Swivel radius
			Fixed	Swivel	Brake			
214 x 59mm (8-7/16" x 2-5/16")	100 kgs (220 lbs)	Pneumatic	1101-08-01-1	1101-08-01-2	—	Ball Bearing	245mm (9-5/8")	Swivel 181mm
200 x 52mm (8" x 2")	100 kgs (220 lbs)	Solid Rubber	1101-08-02-1	1101-08-02-2	—	Ball Bearing	238mm (9-3/8")	Swivel 174mm
262 x 82mm (10-5/16" x 3-1/4")	125 kgs (275 lbs)	Pneumatic	1101-10-01-1	1101-10-01-2	—	Ball Bearing	309mm (12-3/16")	Swivel 190mm
250 x 68mm (10" x 2-11/16")	125 kgs (275 lbs)	Solid Rubber	1101-10-02-1	1101-10-02-2	—	Ball Bearing	303mm (11-15/16")	Swivel 184mm